

MOUNTAIN-PLAINS CONSORTIUM

RESEARCH BRIEF | MPC 22-483 (project 652) | September 2022

Evaluation of Concrete Bridge Deck Mixtures Using Shrinkage-Ring Tests



the **ISSUE**

Concrete is widely used in bridge construction because of its versatility, strength, durability, and low cost. It is a composite consisting of cement, water, coarse aggregates, fine aggregates, and admixtures to engineer the desired properties. During curing, concrete is subjected to changes in volume. These changes can cause cracking, which can allow corrosion and reduce the life of the deck. Maintaining the condition of bridge decks is one of the costliest components of bridge maintenance. There is a need to evaluate the effectiveness of various concrete mixes using different ways to mitigate shrinkage.

the **RESEARCH**

A suite of concrete mixtures using a granitic aggregate was evaluated using the dual-ring test method. This permits the use of coarse and fine aggregates. Results indicate that mitigation methods of fibers and shrinkage-reducing admixtures (SRAs) prolong the time to cracking. The recommendation is to combine both mitigation measures to delay cracking and permit additional tensile strength gains.



A University Transportation Center sponsored by the U.S. Department of Transportation serving the Mountain-Plains Region. Consortium members:

Colorado State University
North Dakota State University
South Dakota State University

University of Colorado Denver
University of Denver
University of Utah

Utah State University
University of Wyoming



Lead Investigator(s)

Jennifer Tanner, PhD
TannerJ@uwyo.edu

Research Assistant(s)

Shamel Perez Buenfil
GRA, PhD

Project Title

Reducing Shrinkage Cracking
in Bridge Decks Using the
Single and Double-Ring Test
Methods

Sponsors | Partners

WYDOT

USDOT, Research and
Innovative Technology
Administration

the FINDINGS

Of the two mitigation measures evaluated, both polypropylene fibers and shrinkage-reducing admixtures served to delay the cracking time. Although the combined mitigation measures did not increase time to cracking, using both mitigation measures is still recommended.

the IMPACT

Findings from the research are expected to be used in formulating the WYDOT specification for concrete placed in new bridge decks. The new specification should reduce shrinkage and cracking and prolong the life of bridge decks and reduce maintenance costs.

For more information on this project, download the main report at <https://www.ugpti.org/resources/reports/details.php?id=1107>

For more information or additional copies, visit the Web site at www.mountain-plains.org, call (701) 231-7767 or write to Mountain-Plains Consortium, Upper Great Plains Transportation Institute, North Dakota State University, Dept. 2880, PO Box 6050, Fargo, ND 58108-6050.



This publication was produced by the Mountain-Plains Consortium at North Dakota State University. The contents of this brief reflect the views of the authors, who are responsible for facts and the accuracy of the information presented herein. This document is disseminated under the program management of the USDOT, Office of Research and Innovative Technology Administration in the interest of information exchange. The U.S. Government assumes no liability for the contents or use thereof.



NDSU does not discriminate in its programs and activities on the basis of age, color, gender expression/identity, genetic information, marital status, national origin, participation in lawful off-campus activity, physical or mental disability, pregnancy, public assistance status, race, religion, sex, sexual orientation, spousal relationship to current employee, or veteran status, as applicable. Direct inquiries to Vice Provost, Title IX/ADA Coordinator, Old Main 201, 701-231-7708, ndsu.eoaa@ndsu.edu.